

## PVC SDR 35/26 Sewer Pipe

Gravity Sewer SDR 35/26 is engineered for non-pressure, gravity-flow sewer applications. The pipe's resistance to chemical corrosion and environmental stressors makes it ideal for residential, commercial, and municipal sewer and stormwater systems.

Applicable Standards: ASTM D1784, ASTM D3034, ASTM D3212, ASTM F679 & ASTM F477

## PVC SDR 35/26 PSM Gravity Sewer Pipe

Nom. Pipe Size (in.)	Outer Diameter (in.)	Wall Thickness (in.)	
		SDR 26 (PS115)	SDR 35 (PS46)
4	4.215	0.162	0.120
6	6.275	0.241	0.180
8	8.400	0.323	0.240
10	10.500	0.404	0.300
12	12.500	0.481	0.360
15	15.300	0.588	0.437
18	18.701	0.671	0.499
21	22.047	0.791	0.588
24	24.803	0.889	0.661
27	27.953	1.002	0.745

- Solid wall pipe with integral gasket joint on each length
- Standard color green and available in 14ft or 20ft lengths
- Pipes and joints are manufactured to ASTM D3034/F679 and ASTM D3212
- Manufactured PVC resin conforming to cell class 12454/12364
- Certified to NSF-14 SW

## **PVC SDR 35 Solvent Weld Sewer Pipe**

SDR 35 solvent weld sewer pipe is designed for non-pressurized underground drainage and sewer applications. It features a smooth interior wall for superior flow and reduced blockages. Solvent weld joints ensure a watertight seal and provide long-lasting performance in gravity-flow systems.

Applicable Standards: ASTM D1784, ASTM D3034

### **PVC SDR 35 Solvent Weld Sewer Pipe**

<b>Nom. Pipe Size (in.)</b>	<b>Outer Diameter (in.)</b>	<b>Wall Thickness (in.)</b>
<b>3</b>	3.250	0.093
<b>4</b>	4.215	0.120
<b>6</b>	6.275	0.180
<b>8</b>	8.400	0.240

- Solid wall pipe with integral solvent weld bell on each length
- Standard color white and available in 10ft or 20ft lengths
- Pipes and bells are manufactured to ASTM D3034
- Manufactured PVC resin conforming to cell class 12454/12364
- Certified to NSF-14 SW